

VI FCP-L2/8

ADDRESSABLE FIRE ALARM CONTROL PANEL



EN54-2 EN 54-4

FEATURES

- ▶ EN54-2 & EN54-4 certified by LPCB and Applus.
- ▶ 7.0 inch color touch-sensitive screen LCD, resolution of 800×480.
- ▶ 324 addresses for 1 loop, max 8 loops.
- ▶ A maximum of 5000 fire protection zones are supported. More user-friendly Night Mode Time Range Settings.
- ▶ Networkable: CAN bus for interconnection of up to 60 FACPs and Ethernet for up to 254 FACPs.
- ▶ Fire alarm, fault, C&E and operation, each category can store up to 10,000 records.

TECHNICAL SPECIFICATION

Mains supply	110/230V AC (-15%,+10%), 50Hz/60Hz
Fuse rating	T4A250V
Max. battery capacity	24AH - 38AH
Max. charging current/voltage	1A / 28VDC
Max. integrated resistance	1Ω
Fire alarm output	20 ~ 28 V DC
F.P.E. output	20 ~ 28 V DC
Probe Output Circuit Output	20 ~ 28 V DC
Fault output	2A @ 24VDC (NC, COM, NO)
24V (+, -)	20 ~ 28 V DC
Output current/voltage	Max. 2A (AUX 24V) 1A (S.C. Out)
Dimensions (WxHxD)	440 x 590 x 180 mm 440 x 590 x 230 mm